

APT IMM24



- The IMM24 has been specifically developed to cope with the constantly high amperage draw found with Immersion heaters and also the wide variety of domestic or industrial timed operations
- BEAB approved, 30 min tappets
- Three programming positions: automatic, permanent on/off
- Surface mounting box containing 2x cable clamps

| Product Code | Specification             | Programming  |
|--------------|---------------------------|--------------|
| IMM24        | 230 V AC 50/60Hz, Surface | Daily/30 min |
| IMM24F       | 230 V AC 50/60Hz, Flush   | Daily/30 min |

APT IMM24EC



- The IMM24 has been specifically developed to cope with the constantly high amperage draw found with Immersion heaters and also the wide variety of domestic or industrial timed operations
- BEAB approved, 30 min tappets
- Three programming positions: automatic, permanent on/off
- Surface mounting box containing 2x cable clamps

| Product Code | Specification    | Programming  |
|--------------|------------------|--------------|
| IMM24EC      | 230 V AC 50/60Hz | Daily/30 min |

UNO



- DIN rail mount, one module wide
- Three programming positions: automatic, permanent on/off
- Protective clear window helps prevent unauthorised handling
- Lateral dial with easy to program tappets

| Product Code | Specification    | Programming  | Battery Backup |
|--------------|------------------|--------------|----------------|
| UNO/D        | 230 V AC 50/60Hz | Daily/15 min | No             |
| UNO/QRD      | 230 V AC 50/60Hz | Daily/15 min | 150 h          |
| UNO/QRS      | 230 V AC 50/60Hz | Weekly/2 h   | 150 h          |

INCA DUO



- DIN rail, two modules wide
- Lateral dial with easy to program tappets
- Two programming positions: automatic and permanent on
- Protective clear window to prevent unauthorised handling

| Product Code | Specification    | Programming  | Battery Backup |
|--------------|------------------|--------------|----------------|
| INCA/DUO/D   | 230 V AC 50/60Hz | Daily/15 min | No             |
| INCA/DUO/QRD | 230 V AC 50/60Hz | Daily/15 min | 100 h          |
| INCA/DUO/QRS | 230 V AC 50/60Hz | Weekly/2 h   | 100 h          |

SUPRA



- DIN rail mount, 2,5 modules wide
- Front dial with easy to program tappets
- Three programming positions: automatic, permanent on/off
- Protective clear window helps prevent unauthorised handling

| Product Code | Specification    | Programming  | Battery Backup |
|--------------|------------------|--------------|----------------|
| SUPRA/D      | 230 V AC 50/60Hz | Daily/15 min | No             |
| SUPRA/QRD    | 230 V AC 50/60Hz | Daily/15 min | 150 h          |
| SUPRA/QRS    | 230 V AC 50/60Hz | Weekly/2 h   | 150 h          |

MINI QRD



- DIN rail, surface or flush/panel mounting
- Front dial is easy to program by movable tappets
- Three programming positions: automatic, permanent on/off
- Sealable window and terminals cover to avoid unauthorised handling

| Product Code | Specification    | Programming  | Battery Backup |
|--------------|------------------|--------------|----------------|
| MINI/QRD     | 230 V AC 50/60Hz | Daily/15 min | 100 h          |

MINI T



- DIN rail, surface or flush/panel mount
- Compact design and installation base with precuts for power supply through cable track or tube when installed on surface
- Front dial with easy to program tappets
- Faston Connections 6.3 x 8mm for flush/panel mounting

| Product Code | Specification    | Programming  | Battery Backup |
|--------------|------------------|--------------|----------------|
| MINI T/D     | 230 V AC 50/60Hz | Daily/15 min | No             |
| MINI T/QRD   | 230 V AC 50/60Hz | Daily/15 min | 100 h          |
| MINI T/QRS   | 230 V AC 50/60Hz | Weekly/2 h   | 100 h          |

ALPHA



- DIN rail, surface or flush/panel mounting
- Front dial is easy to program by movable tappets
- Three programming positions: automatic, permanent on/off
- Faston Connections 6.3 x 08mm for flush/panel mounting

| Product Code    | Specification    | Programming  | Battery Backup |
|-----------------|------------------|--------------|----------------|
| ALPHA/D         | 230 V AC 50/60Hz | Daily/15 min | No             |
| ALPHA/QRD       | 230 V AC 50/60Hz | Daily/15 min | 100 h          |
| ALPHA/QRD/1     | 120 V AC 50/60Hz | Daily/15 min | 100 h          |
| ALPHA/QRD/12VDC | 12 V DC 50/60Hz  | Daily/15 min | 100 h          |
| ALPHA/QRD/24VAC | 24 V AC 50/60Hz  | Daily/15 min | 100 h          |
| ALPHA/QRS       | 230 V AC 50/60Hz | Weekly/2 h   | 100 h          |
| ALPHA/QRS/1     | 120 V AC 50/60Hz | Weekly/2 h   | 100 h          |